

4 EYE FACE LIGHT :WARM WHITE

WATERPROOF



user's guide

Please read through this lamp before using it

catalogue

1.Unboxing to check the..... 02 pages

2.Product Introduction..... 02 pages

3.Product parameter..... 02 pages

4.The interface shows the..... 02 pages

5.Operation and description of the..... Page 03

6.Channel Table..... 05 pages

7 common fault analysis and fault troubleshootingscheme..... 06 pages

Viii.Notes:..... 06 pages

IX.Statement of..... 06 pages

First of all, thank you for choosing your products. Please read this instruction manual carefully and completely, and keep it properly for reference in use.

First, open the box inspection

When receiving the product, please carefully take and put it, check whether the product has any damage caused by transportation, and check the following accessories: lamps- -----4 sets / box manual warranty card-----1 copy product presentation

This lamp is made of new cast aluminum shell, beautiful shape, smooth, fully reflect the characteristics of modern lamp products. The products are designed and produced in strict accordance with CE standards, and fully conform to the international standard DMX512 protocol. They can be controlled by a single station or used by each other, and can adapt to photography, photography, TV stations and other strict lighting requirements.

1. Power: 200W

2.LED beads: 460 w cob beads

3. Lens angle: conventional 25°

4. Color temperature: 3000K-6000K

5. Strobe: random strobe, beating in order, strobe effect (random strobe, beating in order, strobe effect)

6. Heat dissipation: completely cooled by convection through the heat sink

7. Novel design of aluminum casting shell, high-strength tempered glass, streamlined appearance design

8. Control mode: DMX-512 control operation, master-slave mode, single-machine mode, and voice control mode

9. Display: LED digital tube button dial code

10. Waterproof grade: IP65

11. channel:8CH

12. Integrated dimming: 0-100%

13. Strobe: electronic strobe 1-25 fps / s

14. Product size: 240x220x245mm

15. Weight: 4.3 kg

four. Interface display






















1. The MENU menu

















2. UP value

3. DOWN, with decreasing values

4. ENTER Confirmation

Operation and description:

MENU	UP	DOWN	Increase the range value	function declaration	ENTER
	Use the UP or DOWN keys.	↓	 ↕ 	Set the address code	The ENTER key confirms and saves the current value.
			 ↕ 	Various colors change randomly, the larger the 01~50 value, the faster	
			 ↕ 	Various colors flash randomly, the larger the 01~50 value, the faster	
				Sound control mode	
			 ↕ 	The color is all bright (white light) flashing	
				Various colors change randomly.	
			 ↕ 	Red dimming.000~255 The larger the value, the greater the brightness.	

MENU	UP	DOWN	Increase the range value	function declaration	ENTER
	Use the UP or DOWN keys.		  	Green dimming.000~255 The larger the value, the greater the brightness.	The ENTER key confirms and saves the current value.
			  	Blue dimming.000~255 The larger the value, the greater the brightness.	
			  	White dimming.000~255 The larger the value, the greater the brightness.	
			  	Yellow dimming.000~255 The larger the value, the greater the brightness.	

Vi. Channel Table:

order number	function	explain
Channel 1	Total dimming	Linear dimming, from dark to bright 000-255
Channel 2	strobflas h	Strobe speed of 000-255
Channel 3	Is white	Dimmming, linear dimming, from dark to bright 000-255
Channel 4	Is white	Dimmming, linear dimming, from dark to bright 000-255
Channel 5	Warm white	Dimmming, linear dimming, from dark to bright 000-255
Channel 6	Warm white	Dimmming, linear dimming, from dark to bright 000-255
Channel 7	Color temperatu re change	0—255
Channel 8	Functional speed	Functional speed, from slow to fast 000-255

Seven, the common fault analysis and fault troubleshooting scheme

fault phenomenon	failure cause	processing method
1. The display screen of the lamp is not bright, and the fan does not operate	1. Whether the power supply is normal 2. Whether the line is correct	① Correct access to the power supply
2. A lamp is not controlled by the signal	1. The address code is correct 2. Whether the signal line is well connected	① Set the correct address code ② Connect the signal line correctly
3. A lamp or a few color lamp beads are not bright	1. One of the lamp beads may burn out	① renewal

VIII. Notes:

The installation and debugging shall be carried out by professional personnel

The surface of the lamps should not be wiped with dilute solvents such as alcohol

The ambient temperature of lamps should not exceed 40°C, away from fire and flammable items, do not let water wet the lamps

The crane must be equipped with a lamp hook and safety rope that can carry the 10 times the weight of the lamp itself

This lamp shall be kept dry to avoid working in a wet environment.

9. Statement

This product in the factory, the performance is intact, complete packaging. All users shall strictly observe the warnings and operating instructions stated above, any damage caused by misuse is not covered by the Company's warranty and failure and problems caused by the neglect of the operating manual.